



# WebCCTV NVS

## 4 Camera High Performance Network Video Server

**WebCCTV NVS** is a 4-channel stand-alone network video server, which delivers crisp real time live videos at a rate up to 120fps for 4 analog cameras over the TCP/IP network.

**WebCCTV NVS** is a component to be used in conjunction with WebCCTV NVR. Combined with the WebCCTV NVR, it delivers the ultimate solution for video streaming and recording over corporate networks or the Internet.

**WebCCTV NVS** is designed to meet a higher level of TCP/IP based remote video monitoring and security application with high performance frame rate per video channel and a versatile, user-friendly program interface.

**Connect up to 2 WebCCTV NVS units to a single WebCCTV NVR to record up to 8 analog camera sources on a single WebCCTV NVR.** If more WebCCTV NVS units are needed, additional WebCCTV NVR units should be added.

**Use of WebCCTV NVS in conjunction with network cameras.** WebCCTV NVS can be used in conjunction with network cameras making it possible to record analog and network cameras on a single WebCCTV NVR unit.



**WebCCTV NVS**

### KEY FEATURES

- MPEG-4 Compression Engine
- Single or Quadview Analog Monitor Support
- Remote PTZ Camera Control
- Self contained Stable System
- Extended I/O for Sensor & Alarm
- Adjustable Network Bandwidth

## WebCCTV NVS

4 Camera High Performance  
Network Video Server



### SPECIFICATIONS

<b>Video Inputs</b>	4
<b>Video Standards</b>	NTSC
<b>Monitor Inputs</b>	5
<b>Resolution</b>	640 x 480 (NTSC)
<b>Frame Rates</b>	30 fps per camera 120 fps for 4 channels at 320x240 (NTSC)
<b>Compression Techniques</b>	MPEG-4
<b>Advanced service</b>	Advanced services can be obtained by combining the NVS with WebCCTV NVR

**Network protocols** HTTP, TCP/IP, FTP

**Operating System** Windows CE .NET

### CAMERA SUPPORT

**Cameras Supported** Analog NTSC cameras

**Dome Camera Drivers** Panasonic, BBV, Bosch, Dedicated Micros, Ikegami, JVC, Kalatel, LG, Pelco, Sony, Sanyo, Sensormatic, Siemens, Vicon, WebCCTV, Yaan  
(Please check for the latest available drivers)

Product code: WebCCTV-NVS 400



Back Panel

### INTERFACES

<b>LAN</b>	10/100 Mbit, RJ 45
<b>Serial</b>	1 RS 232 port and 1 RS 485 port
<b>Alarm I/O</b>	4 Opto-coupled inputs or 4 digital inputs 4 Relay outputs
<b>Video Output</b>	4 Video loop through per camera input 1 Composite channel (quadview)
<b>Audio</b>	1 Channel Output; 1 Channel Input
<b>USB 1.1</b>	2

### WARRANTY

2 years hardware warranty

### COMPONENT HEALTH SERVICE

Supports watchdog function

### AMBIENT

**Temperature** 5-50°C (40-125°F)

### DIMENSIONS

**H x W x D** 9x 7 x 2.25 in

**Weight** 3.25 lbs

